



CTD Data RV Heincke HE432

Data Processing Report

Contents

1	Introduction	1
2	Workflow	1
3	Cruise details	3
4	Sensor Layout	3
5	Processing	3
6	Results	5

Contact:			
Gerd Rohardt			
Alfred-Wegener-Institute			
Am Handelshafen 12, D-27570 Bremerhaven, GERMANY			
Mail: info@awi.de			
Processing Agency:			
FIELAX			
Schleusenstr. 14, D-27568 Bremerhaven, GERMANY			
Mail: info@fielax.de			
Ref.: CTD-HE432-report.pdf	Vers.: 1	Date: 2016/07/27	Status: final



1 Introduction

This report describes the processing of CTD raw data acquired by Seabird SBE 911plus CTD on board RV Heincke during expedition HE432.

2 Workflow

The different steps of processing and validation are visualized in Figure 1. The CTD raw data are delivered from Gerd Rohardt (AWI). The station book of the RV Heincke cruise is extracted from the DAVIS SHIP data base (https://dship.awi.de). The first CTD station and cast is processed manually in SBE Data Processing to configure the *.psa Seabird routines Data Conversion, Wild Edit, Bottle Summary, Split, Translate, Cell Thermal Mass, Loop Edit and Bin Average. The Seabird routines are then run in a batch job CTDjob in ManageCTD to process the complete CTD data set. The downcast of each CTD station/cast is used for further processing. In CTDjob the start record and the lowest altimeter point of the downcast is selected. With the Utilities \rightarrow Dship Ebook function of ManageCTD the DAVIS SHIP station book extraction is used for getting the header information of all CTD stations/casts of the cruise. ManageCTD Utilities -> Find Profile function compares station times of the header with the entries in the station book to find out the correct naming of the stations and casts. In CTDheader in ManageCTD the header information of each CTD station/cast is displayed, controlled and corrected if necessary. CTDdespike in ManageCTD is used for a visual check of the data and to erase/interpolate spikes in the data if necessary. Additionally, a sensor pair (Temp1/Sal1 or Temp2/Sal2) is chosen for each station/cast of the RV Heincke cruise in CTDdespike.

ManageCTD *Utilities* \rightarrow *CheckDoubleSensors* controls the quality of temperature and conductivity sensors. For this purpose outliers of too high sensor pair differences could be removed. The data is then converted to spreadsheet format with *dsp2odv* for visualization of the data in Ocean Data View (ODV). The second visual inspection of the CTD data allows a comparison with data from other CTD casts from close-by stations to verify the oxygen sensor data. Therefore, potential reference cruise data is downloaded from PANGAEA (http://www.PANGAEA.de). The reference data is converted to *.mat format. In the ManageCTD Final Processing the CTD data is displayed together with the reference data. Bad data points, sensors or casts are interpolated or erased from the data set and filters are applied if necessary. The processed CTD data are written to text files and imported to PANGAEA (http://www.PANGAEA.de) for publication.




Figure 1: CTD data Processing Workflow



3 Cruise details

Vessel name	RV Heincke
Cruise name	HE432
Cruise start	13.09.2014 Bremerhaven
Cruise end	27.09.2014 Bremerhaven
Cruise duration	15 days
No. of CTD casts	34

4 Sensor Layout

This chapter describes the CTD sensors mounted during this cruise: SBE 911plus CTD (SN: 0935), SBE Instrument Configuration Version 7.23.0.1.

ID	Sensor Name	Serial No.	Calibration Date
55	TemperatureSensor	5112	15-Oct-13
3	ConductivitySensor	3570	30-Oct-13
45	PressureSensor	0935	12-Mar-09
55	TemperatureSensor	5101	04-Jan-14
3	ConductivitySensor	3597	03-Jan-14
0	AltimeterSensor	46466	23-Mar-09
20	FluoroWetlabECO_AFL_FL_Sensor	FLRTD-1365	09-Aug-2011
59	TransChelseaSeatechWetlabCStarSensor	435DR	21. Dec 2011
38	OxygenSensor	0467	13-Nov-12

5 Processing

Details of processing procedures and processing parameters are described in *CTD Processing Logbook of RV Heincke* (hdl:10013/epic.47427).

Density Inversions and Manual Validation

Obvius outliers were removed manually. For the visual check density inversions > 0.005 kg/m^3 and > 0.01 kg/m^3 were flagged differently for display but removed automatically. Decisions whether the flagged values were manually removed or not are based on the description in *CTD Processing Logbook of RV Heincke* (hdl:10013/epic.47427).



Sensor Differences




Figure 2: Data accuracy of sensor pairs HE432



6 Results

A complete processing overview for each sensor at each station is summarized in the table in the Appendix (Figure 3).

Double Sensor Check

In Figure 2, the absolute residuals between the two sensorpairs are shown for the measured parameters *Temperature* and *Conductivity* and the derived parameter *Salinity*. Measurements in shallow water depths < 15 m (blue crosses) and gradients between two datapoints exceeding a defined threshold (red crosses) were omitted for accuracy calculation.

	Accuracy	Measurements re-	Remaining measure-
		moved	ments
Parameter	given by manufacturer	Surface 0-15m + gradi-	within accuracy specifi-
		ent filter	cations
Temperature	$\pm 0.001^{\circ}C$	55.65%	79.44%
Conductivity	$\pm 0.003 mS/cm$	51.46%	3.99%
Salinity	$\pm 0.0015 PSU$	49.26%	1.76%

Comments

- 34 CTD/RO "on ground" entries in DShip station book
- 3 CTD casts had no data available
- 33 CTD raw data sets delivered
- 4 CTD casts were invalid or tests (5-6-1t.hex, 18-3_anhang.hex, 11-22.hex, 22-1.hex)
- 0 CTD casts were made twice on a station
- 0 CTD casts had a wrong filename
- 29 CTD casts processed and uploaded
- of these 29 processed CTD casts:
 - 0 oxygen profiles deleted (spiky and not matching to reference casts)
 - 45 data points interpolated
 - 3 data points erased



Result files

Text File (HE432_phys_oce.tab):

Column separator	Tabulator "\t"
Column 1	Event label
Column 2	Date/Time of event
Column 3	Latitude of event
Column 4	Longitude of event
Column 5	Elevation of event
Column 6	DEPTH, water
Column 7	Pressure, water
Column 8	Temperature, water
Column 9	Conductivity
Column 10	Salinity
Column 11	Temperature, water, potential
Column 12	Density, sigma-theta (0)
Column 13	Oxygen
Column 14	Oxygen, saturation
Column 15	Attenuation, optical beam transmission
Column 16	Fluorometer
Column 17	Number of observations

The format is a plain text (tab-delimited values) file.

Processing Report (CTD-HE432-report.pdf):

This PDF document.

Commonte		no blt file available				no data available						no data available				no data available					no blt file available				not enough data points available							not enough data ooints available				
	Offset	1.0 r	1.0	1.0	1.0		1.0	1.0	1.0	1.0	1.0		0.5	0.5	0.5	L	0.6	0.4	0.6	0.6	0.6 r	0.3	0.3	2.0		2.0	1.8	2.0	0.1	0.1	0.1	<u> </u>	2.0	2.0	1.8	
eference	dist. (km)	0.14	0.42	0.48	0.44		45.82	45.11	45.23	45.45	45.50		19.57	19.52	19.41		15.40	0.16	15.55	15.59	0.45	0.19	0.13	2.07		2.39	2.36	2.98	0.22	0.20	0.25		2.26	2.21	2.27	
Oxygen reference	cruise/sss-cc d	HE447/029-1	HE447/029-1	HE447/029-1	HE447/029-1		HE447/029-1	HE447/029-1	HE447/029-1	HE447/029-1	HE447/029-1		HE375/13-1	HE375/13-1	HE375/13-1		HE447/138-1	HE447/127-3	HE447/138-1	HE447/138-1	HE447/127-1	HE447/127-3	HE447/127-3	HE375/01-1		HE375/01-1	HE375/01-1	HE375/01-1	HE375/19-1	HE375/19-1	HE375/19-1		HE375/01-1	HE375/01-1	HE375/01-1	
complete	interp erased	0	•	•	0	0	0	3	•	0	0	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	•	0	я
com	interp	0	•	•	0	0	2	0	ъ	0	1	•	0	0	3	0	1	2	0	0	0	0	3	7	0	8	0	4	0	1	0	0	9	•	2	45
Оху	interp erased							3																												з
Ő									1															1												2
phyll	interp erased																																			0
Chlorophyll									1															1									1			я
Trans	interp erased																																			0
Tra	interp						2		1		1						1	2					3	2												12
Sal	interp erased																																			0
š									1						1									2		4		2		1			2		1	14
du	interp erased																																			0
Temp	interp								1						2									1		4		2					3		1	14
Sensor	pair	2	2	1	1		2	2	1	2	2		2	2	1		1	1	1	2	2	1	1	1		1	2	2	2	2	1		1	2	1	
File	HE432_	1-0.*	1-0-2.*	1-0-4.*	1-0-5.*		5-14-0.*	5-4-0.*	5-5-0.*	5-6-0.*	5-7.*		9-4.*	9-5.*	9-6.*		10-1.*	10-10.*	10-2.*	10-3.*	10-29.*	10-8.*	10-9.*	11-21.*	11-22.*	11-23.*	11-6.*	12-1.*	18-2.*	18-3.*	18-4.*	22-1.*	26-2.*	26-3.*	30-1.*	
Depth	[u]	26.6	27.6	27.4	27.4	28.9	46.3	43.9	44.5	43.4	43.3	44.7	37.6	39.3	39.1	38.9	35.1	24.4	34.9	34.7	25.5	24.2	24.5	22.5	20.6	23.6	23.9	17.8	25.5	26	25	25	24.8	21.8	20	
Position	Longitude	4° 10.23' E	4° 9.97' E	4° 10.01' E	4°9.94'E	4°9.38'E	4° 44.86' E	4° 44.74' E	4° 44.87' E	4° 45.01' E	4° 45.04' E	4° 44.22' E	5° 34.75' E	5° 34.80' E	5° 34.91' E	5° 34.14' E	7° 10.66' E	7° 25.66' E	7° 10.52' E	7° 10.48' E	7° 25.63' E	7° 25.57' E	7° 25.56' E	7° 57.53' E	7° 57.61' E	7° 57.43' E	7° 57.89' E	7° 59.47' E	6° 52.24' E	6° 52.23' E	6° 52.29' E	8°1.18'E	7° 57.88' E	7° 57.52' E	7° 57.41' E	
Position	Latitude	55° 30.01' N	55° 29.98' N	55° 30.22' N	55° 30.11' N	55° 29.88' N	55° 14.99' N	55° 15.53' N	55° 15.52' N	55° 15.43' N	55° 15.41' N	55° 15.41' N	54° 49.83' N	54° 49.83' N	54° 49.86' N	54° 49.64' N	54° 26.28' N	54° 26.33' N	54° 26.31' N	54° 26.31' N	54° 26.53' N	54° 26.37' N	54° 26.34' N	54° 10.35' N	54° 10.38' N	54° 10.53' N	54° 10.45' N	54° 10.13' N	53° 59.16' N	53° 59.17' N	53° 59.18' N	54° 3.80' N	54° 10.40' N	54° 10.43' N	54° 10.47' N	
Timo		02:12	06:05	06:22	06:39	05:54	12:53	06:07	06:27	06:49	07:04	17:33	06:07	06:24	06:41	16:14	12:36	15:55	12:52	13:09	08:07	15:26	15:41	10:07	10:25	10:43	16:05	15:21	06:31	06:48	07:07	12:58	09:17	09:46	06:38	
	המוב	14.09.2014	14.09.2014	14.09.2014	14.09.2014	15.09.2014	CTD/RO 15.09.2014 12:53	CTD/RO 16.09.2014 06:07	16.09.2014	16.09.2014	16.09.2014	16.09.2014	18.09.2014	18.09.2014	18.09.2014	18.09.2014	CTD/RO 19.09.2014	19.09.2014	19.09.2014	19.09.2014	20.09.2014	19.09.2014	19.09.2014	21.09.2014	21.09.2014 10:25	CTD/RO 21.09.2014	20.09.2014	22.09.2014	23.09.2014	23.09.2014	23.09.2014	24.09.2014	25.09.2014	25.09.2014	26.09.2014	
Gear	Abbr.	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	
Station	HE432/	0001-1	0001-3	0001-4	0001-5	0001-31	0005-1	0005-4	0005-5	0005-6	0005-7	0005-23	0009-4	0009-5	9-6000	0009-25	0010-1	0010-10	0010-2	0010-3	0010-30	0010-8	0010-9	0011-21	0011-22	0011-23	0011-6	0012-1	0018-2	0018-3	0018-4	0022-1	0026-2	0026-3	0030-1	








Figure 4: ODV Screenshot of HE432 CTD data Page 8 of 8