



Continuous thermosalinograph oceanography along RV POLARSTERN cruise track PS115.1 (ARK-XXXII/2.1)

Data Processing Report

Contents

| 1 | Introduction | 1 |
|---|-------------------|---|
| 2 | Sensor Details | 1 |
| 3 | Processing Report | 2 |
| 4 | Appendix | 5 |

Contact:

Gerd Rohardt

Alfred-Wegener-Institute

Am Handelshafen 12, D-27570 Bremerhaven, GERMANY

Mail: info@awi.de

Processing Agency:

FIELAX

Gesellschaft für wissenschaftliche Datenverarbeitung mbH Schleusenstr. 14, D-27568 Bremerhaven, GERMANY

Tel: +49 (0) 471 30015 0 Fax: +49 (0) 471 30015 22 Mail: info@fielax.de

 Ref.: PS115.1_TSG.pdf
 Vers.: 1
 Date: 2018/12/14
 Status: final



1 Introduction

This report describes the processing of raw data acquired by the thermosalinographs on board RV Polarstern during expedition PS115.1 to receive cleaned up and corrected salinity data. Detailed description of the processing of the data and the workflow is given in the general report "General Processing Report of Surface T/S Data RV Polarstern Cruises PS106, PS107, PS108 and PS109".

Cruise details

Vessel name: RV Polarstern

Cruise name: PS115.1 (ARK-XXXII/2.1)

Cruise start: 2018-08-05 **Cruise end:** 2018-09-03

Cruise duration: 29 days

Working area: Northeast Greenland

2 Sensor Details

Following sensors were installed during cruise PS115.1. Only data from **TSG1** are uploaded to PAN-GAEA for cruise PS115.1 and are furthermore considered in this report (for reasoning see General Processing Report).

| | TSG1 | TSG2 |
|-----------------------------|------------|------------|
| Serial number | SBE21-3189 | SBE21-3191 |
| Installation | 2018-06-15 | 2018-07-17 |
| Deinstallation | 2018-10-16 | 2018-10-16 |
| Days installed | 123 | 91 |
| External temperature sensor | SBE38-118 | SBE38-137 |



3 Processing Report

Database Extraction

| Data source | DSHIP database (dship.awi.de) |
|------------------------------------|-------------------------------|
| Start of raw file | 2018-08-05T06:00:00 |
| End of raw file | 2018-09-03T06:50:36 |
| Number of lines in hexadecimal raw | 2508637 |
| file | |
| First dataset | 2018-08-06T06:52:02 |
| Last dataset | 2018-09-02T14:02:48 |
| TSG1 valid data | 940703 |

Calculation of 10min means

The calculation of 10min means included the removal of outliers outside a 2-times standard deviation for each data interval. The number of outliers for each parameter are given here.

| Number of outliers >2* | umber of outliers >2*std | | |
|--------------------------|--------------------------|--|--|
| Internal temperature | 30643 | | |
| Conductivity | 28314 | | |
| External temperature | 32241 | | |
| Salinity | 36126 | | |
| Result after outlier rem | oval | | |
| Number 10-min-means | 3918 | | |

Manual flagging

After processing the data were visually inspected. The whole data from a specific timestamp were deleted if there was only one parameter to be manually flagged. **0** data points were manually removed from the TSG1 dataset of PS115.1.

Assigning navigation data

Data from the corrected mastertrack of cruise PS115.1 were assigned to the 10min means of TSG1. A speed filter of 0.5 knots minimum speed is applied to avoid redundant data. See Figure 1 and Figure 2 for the processed and corrected data of TSG1.

Number of speed flags: 471

Number of data in final output file: 3447






Figure 1: 10min means of data from TSG1




Figure 2: Standard deviations of 10min means of data from TSG1



Differences between internal and external temperature of TSG1 temperature sensors

Temperature differences between the internal and the external temperature sensors have to be small under normal circulation conditions. Means and standard deviations for the temperature differences as well as the number of data with a difference larger than 1 °C are given in the following table and are shown in Figure 3.

| | TSG1 temperature difference | | |
|--------------|--------------------------------------|-----------|--|
| | mean \pm standard dev. | no. > 1°C | |
| Spot values | $0.0653 \pm 0.0232^{\circ} \text{C}$ | 0 | |
| 10-min means | $0.0657 \pm 0.0138^{\circ}\text{C}$ | 0 | |





Figure 3: Differences between internal and external temperature sensors of TSG1

Result file

The result file is a plain text (tab-delimited values) file named **PS115.1_surf_oce.tab** with one data row in 10-min interval. For further information on the result file see the General Processing Report.



4 Appendix







Figure 4: Salinity data from TSG1








Figure 5: Temperature data from TSG1